

**ARRI
LIGHTING
GRIP
CATALOGUE**

2004



welcome

ARRI Grip is a comprehensive range of lighting stands and mounting equipment of the highest quality for film, TV and location applications.

Innovative design combined with the latest production technology ensure the quality of these products and makes them worthy of the ARRI name. We listen to you, the practitioners, and adjust the designs accordingly. Recent innovations include time-saving quick-action clamps and folding frames that can be transported without removing the fabric then set up in seconds.



















The products embody practicality and professionalism at all levels, from the captive lock-offs that can't get lost, to the high efficiency brake shoe systems that operate whatever the weather. Precision manufacturing ensures that spares will fit and that parts can be interchanged between stands. Stainless, rust-proofed or aluminium tubes and castings are used throughout.

With the highest regard for safety, all equipment is designed to meet international regulations such as DIN 15560, TUV, CE and ISO.

With a range developed and expanded over more than 30 years, whatever your requirements,

ARRI Grip has the perfect answer.

GUIDE TO SYMBOLS

	Minimum Height
	Maximum Height
	Closed Length
	Footprint Diameter
	Weight
	Maximum Evenly Distributed Load on Level Ground
	Maximum Load on Fully Extended Stand at 6° Inclination
	Spigot Size *
	Socket Size *
	Grip Head Size
	Top Tube Diameter
	Suggested Wheels
	Gravity Cast
	Black Option
	Air Cushioned Option
	Black Chrome Option
	17mm Stand Female Attachment Option
	German Safety Standard

* NOTE: in product specifications you will often see a note referring to the spigot/socket type of the product (e.g. "type 14"). This type number refers to the spigot and socket variants shown on page 105.

Ordering

Products may be ordered by using the product code together with its title.

Optional Black (**B**) finish, Air Cushioned (**AC**), Black Chrome (**CB**) finish and 17mm female attachment (**J**) versions are available where indicated.




Add **B**, **AC**, **CB** or **J** to the product code when ordering.



For stands with maximum load over 3kg, this brochure specifies, in accordance with DIN 15560 norm, the load when the stand is fully extended at an inclination of 6° from vertical.

DIN 15560 specifies the maximum load on a 'non-windup' stand is 18kg. Optional wheels invalidate the height and load specifications according to DIN 15560.

Contents



1 Stands	page 4
2 Clamps	page 44
3 Arms, Brackets & Bars	page 62
4 Grip Head System	page 70
5 Pump Cup & Wall Plates	page 74
6 Lighting Booms	page 78
7 Autopole System	page 86
8 Lighting Control Mountings	page 90
9 Adapters	page 96